



ON-TRACK PLANT ENGINEERING CONFORMANCE CERTIFICATE

This certificate issued in accordance with RIS-1530-PLT Issue 6.

NAME OF CERTIFICATION BODY

ACCREDITATION CODE

AEGIS Certification Services Ltd

AC

Machine Class/Description	Road Rail Machine	Case 988 SP2S	(Type 9B
---------------------------	-------------------	---------------	----------

Vehicle Owner Shovlin Ltd

Issue Date 05 September 2018

Expiry Date 31 August 2025

Vehicle Number: 99709 940513-3

First of Class No

Certificate Number of First of Class NS/0162/17

First of Type No

Certificate Number of First of Type AC/0022/18

Authorised by:

Luigi D'Angelo AEGIS PAB Signatory Official Stamp



Reason for Issue and Scope of Work

Previous Certificate:

RRV originally accepted in accordance with the requirements of RIS-1530-PLT Issue 1. Fitment of direct-acting rail wheel disc brakes certified in accordance with the requirements of RIS-1530-PLT Issue 2.

Plant Asset Manager Copy

Page 1 of 4





This certificate:

Increase in on/off-tracking cant to 150mm. Installation of air brake system. Installation of GKD RCI System. Upgrade to RIS-1530-PLT issue 6. Increase number of towed trailers to 4.

Deviations Associated with this Certificate

Reference None **Title** None

Previous Certificate Number: RT/EA/0138/12

Approved Maintenance Instructions

ID No.	Title					Issue No.	Date
SPMM0001	Case	988	Rail	Mounted	Excavator	6	March
	Opera:	tion an	d Main	itenance Ha	ndbook		2018
AJH080	Hydrov	Hydrovane Compressor Maintenance 1		1	22/04/2014		

Machine Data

Gross Mass	21,800 kg		
Tailswing gauge exceedance	580 mm	Tailswing Height	1430 mm
Hydraulic park brake pressure	0-60 bar	Hydraulic service brake pressure	60 bar
Air service brake pressure	8.5 bar	Air park brake pressure	8.5 bar
Gauge	W6a	Software version (inc. RCI)	9.28

Approved Values

Maximum number of people	2		
Main load lifting point SWL	10,000 kg	Auxiliary lifting point SWL	5,000 kg
Maximum towed load	46000 kg	Maximum number of trailers	4

Approved Track Conditions

	Travelling Mode	Working Mode	On/off-tracking
Maximum gradient	1:25	1:25	1:25
Maximum cant	200 mm	150 mm	150 mm
Minimum curve radius	80 m	80 m	

Plant Asset Manager Copy

Page 2 of 4





Approved Maximum Speeds

	Travelling Mode	Working Mode
Plain Line	10 mph	10 mph
Switches and Crossings	5 mph	5 mph
Raised check and guard rails	5 mph	5 mph
Reverse	5 mph	5 mph
Towing	10 mph	10 mph

Limitations of Use

- 1. The machine shall not be used outside a possession.
- 2. The maximum number of people transported on this machine shall not exceed the value given in the Approved Values section of this ECC.
- 3. Lifts shall not exceed any SWL given in the Approved Values section of this FCC.
- 4. The maximum towed load shall not exceed the value given in the Approved Values section of this ECC.
- 5. The maximum number of trailers shall not exceed the number given in the Approved Values section of this ECC.
- 6. The machine shall not be used on track conditions in excess of those given in the Approved Track Conditions section of this ECC.
- 7. The machine speed shall not exceed the values given in the Approved Maximum Speeds section of this ECC.
- 8. The machine shall only be on/off-tracked at a RRAP or temporary crossing.
- 9. When travelling, mirrors shall be folded in.
- 10. When working, the counterweight, boom, dipper and attachments can be out of gauge. See Machine Data section of this ECC.
- 11. The machine shall **NOT** on/off-track, travel or work on live conductor-rail lines.
- 12. For access/egress, the machine may only operate with the door to the cab adjacent to a cess or a line closed to all train movements or the Method Statement safe system of work must take account of adequate safe clearances to adjacent lines.
- 13. Movement of boom towards backward stability limit shall be at moderate/low speed.

Supplementary Information

- 1. This machine's / re-approval for seven years was assessed against RIS-1530-PLT issue 6.
- 2. Duty chart reference: Case 988 232259 YTZ 1.80m+3.13m+2.10m 3 Sept 2018.
- 3. Machine is a rail-conversion of road multi-purpose excavator with 1.8m boom, 3.13m artic and 2.1m dipper arm.
- 4. It may work with a range of attachments through the dipper arm link pins or approved auxiliary lifting point.

Plant Asset Manager Copy





5. The machine is fitted with a low performance vertical and lateral Movement Limiting Device.

Chassis / Serial Number	CGG0232259
Fleet Number	YTZ
Rexquote Number	1591

Authorised by:	

Luigi D'Angelo AEGIS PAB Signatory